



JC400P

Integrated Dual-Channel DashCam

With a highly integrated design, JC400P 4G dashcam comes with a 1080P front camera that records everything on the road and in the cabin. Furthermore, the 4G capability of the device enables seamless video streaming, live audio alerts, route replay, and video history playback. With all of these features, fleet managers can coach drivers based on data and improve operations to unlock more benefits, whether they're managing government, logistics, ride-hailing, or taxi fleets.



Taxi Service



Online Ride-hailing



Logistics Service



Hazmat Trucking



Video Surveillance

Powerful LTE connectivity enables the live monitoring of the vehicle's interior and exterior via an online platform; while the critical video clips in the device allows for on-demand playback after the fact from anywhere, at any time.



Dual-Channel Recording

Simultaneously monitor the road ahead and what happens in the cab in real-time through the two on-device lenses, with no peripheral camera needed.



Multiple Alerts

Record and upload video clips or still images of customizable events such as speeding and SOS button activation.



Compact Size

The small form factor allows discreet installation behind the rearview mirror without blocking the driver's view.



Vehicle Immobilization

Enable you to cut off the fuel/power to the vehicle moving under 20km/h using Tracksolid Pro, which is useful if your fleet vehicle has been stolen.



Fast Integration

We can provide an IoT Hub to facilitate fast and seamless integration to any third-party platform or the intelligent transport system (ITS).

Specifications

Cellular

Technology	4G LTE Cat 4, 3G (WCDMA), 2G (GSM) JC400P: LTE-FDD: B1/B3/B5/B7/B8/B19/B20 LTE-TDD: B38/B39/B40/B41 (100M) WCDMA: B1/B2/B5/B8 GSM: B2/B3/B5/B8
Frequency	JC400P-A: LTE-FDD: B2/B3/B4/B5/B7/B12/B17 LTE-TDD: B38/B41 (100M) WCDMA: B2/B4/B5 GSM: B2/B5/B8

GNSS

Positioning system	GPS, BDS
---------------------------	----------

Camera

Front camera (main)	1920x1080/25FPS/F2.2/Full color/118° (HfOV)
Sub camera	1280x720/15FPS/F2.5/Color in daytime & mono in dim light/90° (HfOV)
Video format	.mp4

Power

Input voltage	DC 9–30V
Backup battery	450mAh

Operating environment

Operating temperature	–20°C to +65°C
Storage temperature	–30°C to +85°C

Interface

LED indication	Red (Power), Blue (Cellular), Green (GNSS)
SIM	Nano-SIM
External memory	TF card (up to 256GB)
USB	Micro-USB
WiFi	2.4GHz, Support AP Mode/STD Mode/WiFi Direct
Bluetooth	BLE 4.0
Microphone	Support
Speaker	Support
Digital I/Os	1*SOS, 1*Relay
Analog I/Os	N/A
Serial ports	1*RS232
Sensor	6-Axis accelerometer & gyroscope

Feature

ADAS	N/A
DMS	N/A
Configuration support	GPRS, SMS, Memory card, APP
Firmware update	USB cable, Memory card, OTA
Certification	CE, FCC, RoHS

Physical specification

Dimensions	109,0 x 69,0 x 52mm
Weight	233g

Standard Packing

JC400P unit	1	Mount base	1	Tamper cover	1
Power cable (no RS232)	1	Double-sided adhesive	1	Phillips screwdriver	1
SOS button	1	Screws	1	Power bank	1
12V Relay	1	Ejector pin	1		

Optional Configuration*

24V Relay	Instead of 12V relay
Power cable with RS232 support	
OBD power cable	
RS232 sensor	Fuel sensor, RFID reader, Magnetic card reader, Temperature sensor
Tamper lock	Protect against unauthorized removal of SIM and TF cards
Bracket	For medium-duty or heavy-duty trucks based on your specific needs

*Optional Configuration required to be customized or purchased separately.